

Which Options are available for DT-930?

Applies to: DT-930

Status: Resolved

DT-930 Model Types	
Description	Remarks
DT-930M50E	reading angle downward 60°
DT-930M51E	reading angle straight
Battery	
DT-923LI	Lithium-Ion battery
Cradles / Battery Chargers	
DT-960IOE	Cradle with I/O Interface AC Adaptor AD-S10095AE + cable DT-787G required
DT-969CHGE	Cradle, only charging function AC Adaptor AD-S10095AE required
DT-964IOE	Cradle with I/O Interface + charging function AC Adaptor AD-S42120BE + cable DT-887AXA required
HA-E60IO	USB communication cradle AC Adaptor AD-S15050BE AD-S42120BE required + cable DT-380USB
AC Adaptors	
AD-S10095AE	for DT-960IOE / DT-969CHGE
AD-S42120BE	for DT-964IOE
AD-S15050BE	for HA-E60IO
Cables	
DT-787G	between DT-960IOE and PC
DT-887AXA	between DT-964IOE and PC
DT-380USB	between HA-E60IO and PC
Accessories	
HA-E90BP	Bumper Set for extra strength against drop impact
DT-930GUISDK	Development environment

For more information on this or other articles, contact us at: <http://www.casio-b2b.com/mis/de/contact/>

© 2011 CASIO Europe GmbH

The article is provided as a service to current and perspective CASIO customers. Trademark references made to various companies and their products belong to the respective companies. All information is provided as is.

CASIO Europe GmbH

Casio-Platz 1
22848 Norderstedt
Germany

Fon +49 40 / 528 65-0
Fax +49 40 / 528 65-100

Local court: Kiel, HRB 3315
U.St.ID-No.: DE 118536381
WEEE Reg. No. DE 87608106
Managing Director: Kazuyuki Yamashita
Deputy Managing Director: Yoshiyuki Kuroda